

- Minimum of 6'-0" from center to center of bulls eyes on adjacent dart machines.
- Tape has been placed to mark the front edge of the dart machine.
- Sloping dimension of 9'-9 5/8" from center of bulls eye to front edge of tape line.
- Spider and segments are in acceptable condition.
- Dart machine is reasonably level & plumb.

I certify this dart machine at the sponsor location of _____ meets the criteria checked above and is acceptable for use in League Competition.

Certified by _____ Date of Certification _____

- Minimum of 6'-0" from center to center of bulls eyes on adjacent dart machines.
- Tape has been placed to mark the front edge of the dart machine.
- Sloping dimension of 9'-9 5/8" from center of bulls eye to front edge of tape line.
- Spider and segments are in acceptable condition.
- Dart machine is reasonably level & plumb.

I certify this dart machine at the sponsor location of _____ meets the criteria checked above and is acceptable for use in League Competition.

Certified by _____ Date of Certification _____

- Minimum of 6'-0" from center to center of bulls eyes on adjacent dart machines.
- Tape has been placed to mark the front edge of the dart machine.
- Sloping dimension of 9'-9 5/8" from center of bulls eye to front edge of tape line.
- Spider and segments are in acceptable condition.
- Dart machine is reasonably level & plumb.

I certify this dart machine at the sponsor location of _____ meets the criteria checked above and is acceptable for use in League Competition.

Certified by _____ Date of Certification _____